

# Patent Abstracts of Japan

PUBLICATION NUMBER : 03248077  
PUBLICATION DATE : 06-11-91



APPLICATION DATE : 27-02-90  
APPLICATION NUMBER : 02046393

APPLICANT : FUJITSU LTD;

INVENTOR : FUJIKAWA SHINICHI;

INT.CL. : G01S 7/32 G01S 13/53

TITLE : RADAR SIGNAL PROCESSING SYSTEM



ABSTRACT : PURPOSE: To detect a target accurately without penetration of a point clutter by turning an averaging cell of a Constant False Alarm Rate (CFAR) blank or to other conditions by a signal obtained by a clutter map.

CONSTITUTION: A radar signal is turned with a moving target indicator (MTI) 3 to a non-zero Doppler signal to be supplied to an FFT Doppler filter 4. A Doppler frequency per Doppler bank set here is selected to be picked up at each Doppler bank with an improved S/N. An output of the filter 4 is compared with thresholds by CFARs 20<sub>0</sub>-20<sub>MAX</sub> and the non-zero Doppler signal of the Doppler bank with a level thereof exceeding the threshold is detected and judged to be a target. A threshold/averaging cell control circuit 21 judges a state exceeding a certain level according to a map condition of a clutter map 2 to be a point clutter. The resulting judgement signal is supplied to the CFARs 20<sub>0</sub>-20<sub>MAX</sub> to turn an averaging cell blank corresponding to a range pin R<sub>n</sub> among the averaging cells 13<sub>1</sub>-13<sub>2</sub> of the CFAR of a bank N.

COPYRIGHT: (C)1991,JPO&Japio